



OVARO C_{UD}

LAMINATED BOARD WITH TWO SIDES IN COLOURED PAPER

TECHNICAL SPECIFICATION

SEPTEMBER 2020

SUBSTANCE	CALIPER	BULK
ISO 536	ISO 534	ISO 534
g/m²	mm	cm³/g
715	1.00	1.40
800	1.20	1.50
880	1.30	1.48
960	1.50	1.56

BRIGHTNESS		
TOP	/	ISO 2470
BACK	/	ISO 2470

TOLERANCES - SAMPLING ISO 186		
SUBSTANCE	+/- 5%	average of order
MOISTURE ISO 287	7.0% + 2 / - 1	average of order
CALIPER	+/- 5%	for single determinations (95% of values)
BRIGHTNESS	/	for single determinations (95% of values)
TEST CONDITIONS	T: 23° C +/- 1	RH: 50% +/- 2

C22 TWO SIDE COLOURED **YELLOW / YELLOW**

C44 TWO SIDE COLOURED **RED / RED**

C66 TWO SIDE COLOURED **GREEN / GREEN**

C88 TWO SIDE COLOURED **SKY BLUE / SKY BLUE**

C99 TWO SIDE COLOURED **BLACK / BLACK**

C20 TWO SIDE COLOURED **YELLOW / WHITE**

C40 TWO SIDE COLOURED **RED / WHITE**

C60 TWO SIDE COLOURED **GREEN / WHITE**

C80 TWO SIDE COLOURED **SKY BLUE / WHITE**

C09 TWO SIDE COLOURED **WHITE / BLACK**

CERTIFICATIONS: ISO 9001 / ISO 14001 / ISO 50001 / OHSAS 18001
FSC® C081817 - PEFC™ INT-PEFC/COC-001142 CERTIFIED BOARD IS AVAILABLE ON REQUEST

To download the certificate, please click